



Temp. Range: -10 °C to 65°C

Applications: drawing and conveying water, oil and powder in factory, agriculture, building.

Construction:

(1) Transparent and good cold and hot resistance.

(2) Small bending radius and great ability of minus pressure resistance.

Part No.	size	Inner Diameter		Outer Diameter		Weight		Length (m/coil)
		inch	mm	inch	mm	lb./ft.	kg/m	
SHR0610	1/4"	0.236	6	0.394	10	0.046	0.068	100
SHR0611		0.236	6	0.433	11	0.060	0.090	100
SHR0612		0.236	6	0.472	12	0.078	0.116	100
SHR0812	5/16"	0.315	8	0.472	12	0.058	0.086	100
SHR0813		0.315	8	0.512	13	0.075	0.112	100
SHR0814		0.315	8	0.551	14	0.094	0.140	100
SHR0913	3/8"	0.354	9	0.512	13	0.063	0.094	100
SHR0914		0.354	9	0.551	14	0.082	0.122	100
SHR1014		0.394	10	0.551	14	0.068	0.102	100
SHR1015		0.394	10	0.591	15	0.090	0.134	100
SHR1016		0.394	10	0.630	16	0.111	0.166	100
SHR1216	1/2"	0.472	12	0.630	16	0.080	0.120	100
SHR1217		0.472	12	0.669	17	0.103	0.154	100
SHR1218		0.472	12	0.709	18	0.129	0.192	100
SHR1317		0.512	13	0.669	17	0.086	0.128	100
SHR1318		0.512	13	0.709	18	0.111	0.166	100
SHR1319		0.512	13	0.748	19	0.137	0.204	100
SHR1519	5/8"	0.591	15	0.748	19	0.098	0.146	50
SHR1520		0.591	15	0.787	20	0.125	0.186	50
SHR1521		0.591	15	0.827	21	0.154	0.230	50
SHR1620		0.630	16	0.787	20	0.103	0.154	50
SHR1621		0.630	16	0.827	21	0.133	0.198	50
SHR1622		0.630	16	0.866	22	0.164	0.244	50
SHR1923	3/4"	0.748	19	0.906	23	0.121	0.180	50
SHR1924		0.748	19	0.945	24	0.154	0.230	50
SHR1925		0.748	19	0.984	25	0.189	0.282	50
SHR1926		0.748	19	1.024	26	0.225	0.336	50
SHR2024		0.787	20	0.945	24	0.126	0.188	50
SHR2025		0.787	20	0.984	25	0.161	0.240	50
SHR2026		0.787	20	1.024	26	0.197	0.294	50
SHR2027		0.787	20	1.063	27	0.236	0.352	50
SHR2529	1"	0.984	25	1.142	29	0.154	0.230	50
SHR2530		0.984	25	1.181	30	0.197	0.294	50
SHR2531		0.984	25	1.220	31	0.240	0.358	50
SHR2532		0.984	25	1.260	32	0.286	0.426	50
SHR3238	1-1/4"	1.260	32	1.496	38	0.300	0.448	40
SHR3239		1.260	32	1.535	39	0.355	0.530	40
SHR3240		1.260	32	1.575	40	0.412	0.614	40
SHR3241		1.260	32	1.614	41	0.471	0.702	40
SHR3845	1-1/2"	1.496	38	1.772	45	0.416	0.620	40
SHR3846		1.496	38	1.811	46	0.482	0.718	40
SHR3847		1.496	38	1.850	47	0.547	0.816	40
SHR3848		1.496	38	1.890	48	0.616	0.918	40
SHR5058	2"	1.969	50	2.283	58	0.618	0.922	40
SHR5059		1.969	50	2.323	59	0.703	1.048	40
SHR5060		1.969	50	2.362	60	0.787	1.174	40
SHR5061		1.969	50	2.402	61	0.875	1.304	40
SHR5062		1.969	50	2.441	62	0.962	1.434	40