



**Temp. Range:** -10 °C to 65°C

**Applications:** widely used for some pneumatic tools, pneumatic washing apparatus, compressors, engine components, machinery service tools, pesticide spraying apparatus and civil engineering pneumatic hammers.

**Construction:**

- (1) Adopting qualified PVC synthesis materials with built-in reinforced fiber.
- (2) Light weight, easy to handle.
- (3) Applicable to all kinds of air pumps and air compressors.

Part No.	size	Inner Diameter		Outer Diameter		Weight		Working pressure		Length (m/roll)
		inch	mm	inch	mm	lb./ft.	kg/m	Psi	Mpa	
SHA06512	1/4"	0.26	6.5	0.47	12	0.0731	0.109	290	2.0	100
SHA07513	9/32"	0.30	7.5	0.51	13	0.0812	0.121	290	2.0	100
SHA08514	5/16"	0.33	8.5	0.55	14	0.0892	0.133	290	2.0	100
SHA1016	3/8"	0.39	10	0.63	16	0.1127	0.168	290	2.0	100
SHA1320	1/2"	0.51	13	0.79	20	0.1663	0.248	290	2.0	100
SHA1625	5/8"	0.63	16	0.98	25	0.2663	0.397	290	2.0	100
SHA19285	3/4"	0.75	19	1.12	28.5	0.3253	0.485	290	2.0	100
SHA25345	1"	0.98	25	1.36	34.5	0.4078	0.608	218	1.5	50
SHA03244	1-1/4"	1.26	32	1.73	44	0.658	0.981	218	1.5	50
SHA03850	1-1/2"	1.50	38	1.97	50	0.762	1.136	218	1.5	50
SHA05064	2"	1.97	50	2.52	64	1.151	1.716	145	1.0	50



**Temp. Range:** -10 °C to 65°C

**Applications:** Drawing and conveying water, oil and powder in factory, agriculture, building.

**Construction:**

- (1) Transparent and good cold and hot resistance.
- (2) Small bending radius and great ability of minus pressure resistance.

Part No.	size	Inner Diameter		Outer Diameter		Weight		Length (m/roll)
		inch	mm	inch	mm	lb./ft.	kg/m	
SHC0608	1/4"	0.24	6	0.31	8	0.018	0.027	100
SHC1012	3/8"	0.39	10	0.47	12	0.029	0.043	100
SHC1215	1/2"	0.47	12	0.59	15	0.054	0.08	50
SHC1518	5/8"	0.59	15	0.71	18	0.064	0.096	50
SHC1922	3/4"	0.75	19	0.87	22	0.080	0.12	50
SHC2530	1 "	0.98	25	1.18	30	0.180	0.268	50
SHC3238	1-1/4"	1.26	32	1.50	38	0.220	0.328	50
SHC3844	1-1/2"	1.50	38	1.73	44	0.322	0.48	40
SHC5058	2 "	1.97	50	2.28	58	0.567	0.845	40