



**Temp. Range:** -5 °C to 90°C

**Applications:** PVC Hose used for shower and sanitary wares.

**Construction:**

- (1) It is made by fitting couplings at the ends of PVC hose, colorful and artistic,
- (2) It is Non-toxic, heat resistance, resistance to high pressure, long service life.

Part No.	Size	Metric Measurement		Length	Working Pressure		Burst Pressure		Weight	Packing Size	Cubage
	Inch	I.D.mm	O.D.mm	M/Coil	Psi	Bar	Psi	Bar	KG/Coil	D×H(mm)	m <sup>3</sup> /coil
SHSH0814	5/16"	8	14	100	145	10	435	30	14.1	460×150	0.032
SHSH8514		8.5	14	50	145	10	435	30	6.7	345×150	0.018
SHSH0914	3/8"	9	14	100	145	10	435	30	12.3	445×160	0.032
SHSH9514		9.5	14.5	50	217	15	652	45	6.5	345×150	0.018



**Temp. Range:** -5 °C to 65°C

**Applications:** The hose is widely used in pneumatic tools, pneumatic washing apparatus, engine components, machine service and civil engineering equipments.

**Construction:**

- (1) Being made of three layers of PVC materials and high tensile polyester reinforcement with two layers, this hose can work under very high working pressure.
- (2) It is light, flexible, durable, anti-erosion, and explosion resistant.

Part No.	Size	Metric Measurement		Working Pressure		Burst Pressure		Length	Weight		Packing Size	Cubage
				At 23°C					M/coil	lb./ft.		
	Inch	I.D.mm	O.D.mm	Psi	MPa	Psi	MPa	m <sup>3</sup>				
SHSP8135	5/16"	8	13.5	580	4	2320	16	100	0.087	13	390×220	0.033
SHSP0915	3/8"	9	15	435	3	1740	12	100	0.101	15	460×220	0.047
SHSP1016	13/32"	10	16	435	3	1740	12	100	0.111	16.5	480×180	0.041
SHSP1218	1/2"	12	18	435	3	1740	12	100	0.127	19	480×250	0.058
SHSP1522	5/8"	15	22	290	2	1160	8	100	0.181	27	560×250	0.078
SHSP1927	3/4"	19	27	290	2	1160	8	50	0.268	20	550×190	0.059