



Rubber Air Hose



Tube: black, smooth, synthetic rubber

Reinforcement: high tensile synthetic yarn braided or spiraled

Cover: black or red, smooth (wrapped finish) synthetic rubber, abrasion, weather and abrasion resistant

Application: for a variety of general purposes in industries, construction sites and mines.

Temp. Range: -35°C to 80°C

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	1.0~2.0	145~290	3.0~6.0	430~870	0.13	100±1%
6	1/4"	13	1.0~2.0	145~290	3.0~6.0	430~870	0.15	100±1%
8	5/16"	15	1.0~2.0	145~290	3.0~6.0	430~870	0.23	100±1%
10	3/8"	17	1.0~2.0	145~290	3.0~6.0	430~870	0.26	100±1%
13	1/2"	22	1.0~2.0	145~290	3.0~6.0	430~870	0.36	100±1%
16	5/8"	25	1.0~2.0	145~290	3.0~6.0	430~870	0.53	100±1%
19	3/4"	29	1.0~2.0	145~290	3.0~6.0	430~870	0.64	100±1%
25	1"	36	1.0~2.0	145~290	3.0~6.0	430~870	0.85	100±1%
32	1.1/4"	43	1.0~2.0	145~290	3.0~6.0	430~870	1.2	50±1%
38	1.1/2"	50	1.0~2.0	145~290	3.0~6.0	430~870	1.39	50±1%
51	2"	65	1.0~2.0	145~290	3.0~6.0	430~870	1.8	50±1%



Rubber Water Hose



Tube: black, smooth, synthetic rubber

Reinforcement: high tensile synthetic yarn braided or spiraled

Cover: black or green, smooth (wrapped finish) synthetic rubber, abrasion, weather and abrasion resistant

Application: for a variety of general purposes in industries, construction sites and mines.

Temp Range: -35°C to 80°C

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	0.3~1.0	45~145	0.9~3.0	130~430	0.13	100±1%
6	1/4"	13	0.3~1.0	45~145	0.9~3.0	130~430	0.15	100±1%
8	5/16"	15	0.3~1.0	45~145	0.9~3.0	130~430	0.23	100±1%
10	3/8"	17	0.3~1.0	45~145	0.9~3.0	130~430	0.26	100±1%
13	1/2"	22	0.3~1.0	45~145	0.9~3.0	130~430	0.36	100±1%
16	5/8"	25	0.3~1.0	45~145	0.9~3.0	130~430	0.53	100±1%
19	3/4"	29	0.3~1.0	45~145	0.9~3.0	130~430	0.64	100±1%
25	1"	36	0.3~1.0	45~145	0.9~3.0	130~430	0.85	100±1%
32	1.1/4"	43	0.3~1.0	45~145	0.9~3.0	130~430	1.2	50±1%
38	1.1/2"	50	0.3~1.0	45~145	0.9~3.0	130~430	1.39	50±1%
51	2"	65	0.3~1.0	45~145	0.9~3.0	130~430	1.8	50±1%