

Fabric Reinforced Steam Hose



Applications : For intermittent conveying saturated vapour or superheated water at a temperature below 175°. The vapour pressure above 0.4 MPa is not allowed.

Features : Made of excellent heat resistant rubber and materials. It is safe for use.

Factor of safety : 5

I. D.		Fabric	W. P.	B. P.	LENGTH
MM	INCH	Ply.	MPA	MPA	M/ROLL
16	5/8"	4~7	0.5~1.0	2.5~5.0	20
19	3/4"	4~7	0.5~1.0	2.5~5.0	20
25	1"	5~7	0.5~1.0	2.5~5.0	20
32	1.1/4"	5~7	0.5~1.0	2.5~5.0	20
38	1.1/2"	5~8	0.5~1.0	2.5~5.0	20
51	2"	6~10	0.5~1.0	2.5~5.0	20
64	2.1/2"	6~10	0.5~1.0	2.5~5.0	20
76	3"	6~10	0.5~1.0	2.5~5.0	20
89	3.1/2"	6~12	0.5~1.0	2.5~5.0	20
102	4"	6~12	0.5~1.0	2.5~5.0	20
127	5"	6~12	0.5~1.0	2.5~5.0	20
150	6"	6~12	0.5~1.0	2.5~5.0	20

Fabric Reinforced Acid-alkali Hose



Applications : For conveying sulphuric acid with a concentration below 40% and other inorganic acids (except nitric acid) as well as dilute alkaline solutions at room temperature.

Features : Made of excellent chemical corrosion resistant rubber and other special materials, possessing good acid-alkali resistance.

Factor of safety : 4

I. D.		Fabric	W. P.	B. P.	LENGTH
MM	INCH	Ply.	MPA	MPA	M/ROLL
13	1/2"	2~3	0.5~1.0	2.0~4.0	20
16	5/8"	3~4	0.5~1.0	2.0~4.0	20
19	3/4"	3~7	0.5~1.0	2.0~4.0	20
25	1"	4~7	0.5~1.0	2.0~4.0	20
32	1.1/4"	4~7	0.5~1.0	2.0~4.0	20
38	1.1/2"	4~8	0.5~1.0	2.0~4.0	20
51	2"	5~10	0.5~1.0	2.0~4.0	20
64	2.1/2"	5~10	0.5~1.0	2.0~4.0	20
76	3"	5~10	0.5~1.0	2.0~4.0	20
89	3.1/2"	5~12	0.5~1.0	2.0~4.0	20
102	4"	5~12	0.5~1.0	2.0~4.0	20
127	5"	5~12	0.5~1.0	2.0~4.0	20
150	6"	5~12	0.5~1.0	2.0~4.0	20

Sand Blast Hose



Applications : For sand-blasting and eliminating rust on the surface of metal parts.

Features : The inner tube is made of excellent wear-resistant rubber, possessing good pressure resistance.

Factor of safety : 4.

I. D.		O. D.	W. P.	B. P.	LENGTH
MM	INCH	MM	MPA	MPA	MAX. M/ROLL
16	5/8"	29	1	3	60
19	3/4"	35	1	3	60
25	1"	39	1	3	60
32	1.1/4"	49	1	3	60
38	1.1/2"	55	1	3	60
38	1.1/2"	60	1	3	60
51	2"	71	1	3	60
64	2.1/2"	85	1	3	60
76	3"	97	1	3	60
89	3.1/2"	103	1	3	60
102	4"	129	1	3	40